

# Microwave Instrument Update

Bjorn Lambrigtsen Frank Sun Steve Broberg

Jet Propulsion Laboratory
California Institute of Technology





# **Topics**

- Instrument status
- Changes for V4
- Scan bias analysis
- Plans for V5





#### **Microwave Instrument Status**

#### AMSU-A

- Two channels have experienced slowly declining gain
- Recently many -A2 temperature sensors became very noisy

#### HSB

- Still not working
  - The plan is to put in place a procedure to try periodic re-starts
  - Procedure expected to be in place early next year
  - Last "kick-start" attempt was on January 16, 2004





#### **AMSU Gain Variation: Ch. 4-6**

(More in backup slides)


# Channel 4 shows negligible gain change

Channel 5 shows 8%/year gain decline

Channel 5 also showed 5% drop after solar flare

Channel 6 shows 4%/year gain decline


#### Shown: calibration coefficient $a_1 \approx 1/gain$








### **AMSU-A2 Anomalous Temperatures**






All instrument-PRT readings became very noisy on November 16 (Also "PRT Ref Voltage")
All warm load readings are still good

This is currently under investigation at JPL and NGES





## **No Anomalous Brightness Temperatures**



Start of anomaly is not discernible







### **Preliminary Anomaly Assessment**

- No effect on calibration or Tb's can be discerned
- This is expected:
  - Only "RF shelf T" is used besides the warm load T's
  - It is used to interpolate lookup tables
    - Warm load correction
    - Nonlinearity correction
  - Both corrections are very small
    - A 3 K T-error translates into << 1 K</li>
- Nevertheless, we may put in place a quick fix:
  - Either smooth RF-shelf-T
    - Downside: requires a very wide window (many granules)
  - Or find a substitute T
    - Looking at "RF-shelf-T" ≈ a + b Warm-load-T (by regression)
  - Or use Passive-Analog instrument-T
    - Downside: Sampled only every 8th scan line





### Microwave L1b Changes in V4

#### Only minor changes

- Two Tb slots (implemented in V3.5)
  - Antenna temperatures (Ta): radiometrically calibrated Tb's
  - Brightness temperatures (Tb): scan bias corrected Ta
  - Tb is currently identical to Ta (awaiting bias correction)
- Narrower window for "moon-in-FOV" flag
- Fix for data gaps when moon appears in cold-cal FOV
  - All cold-cal looks affected when moon is in FOV
  - Therefore: cannot compute calibration coefficients
  - Normally: use last valid coefficients
  - But: coefficients do not get carried across granule boundaries
  - Moon-in-FOV can last for up to ~2 granules
  - This has caused data gaps for prolonged moon encounters
  - Fix: bridge across granule boundaries






# **AMSU Scan Bias Analysis Using AIRS**

- Objective is definitive scan bias characterization
  - Identify best "truth" for "obs-sim"
  - Determine empirical relative scan bias and absolute nadir bias
  - Compare with modeled scan bias
  - Compare with AIRS
- All analysis shown is for clear/ocean/±30°/Sep.6'02






# Scan Bias Example: Channel 6








# **Scan Bias Example: Channel 12**







# **Equivalent AIRS Channels**




Tb at peak of weighting function - Weighting functions for standard atmosphere





#### AMSU & AIRS obs & sim vs. scan: Ch. 6








#### AMSU & AIRS obs & sim vs. scan: Ch. 12


(More in backup slides)








# AMSU & AIRS obs-calc summary: Nadir







# Sim[ECMWF] vs. Sim[AIRS]: Ch. 6








# Sim[ECMWF] vs. Sim[AIRS]: Ch. 12

(More in backup slides)








#### obs-sim[AIRS] vs. obs-sim[ECMWF]

(More in backup slides)

#### **Channel 13**








#### **Scan Bias Correction Coefficients**


(More in backup slides)

#### **Channel 6**












































































#### **Conclusions and Further Work**

- Empirical bias corrections look good
- May be "best" tuning, but need to be tested on wider data
  - Coefficients derived from "clear/ocean/±30°/Sep.6'02"
  - Tested on "all/±80°/Sep.6'02"
- Coefficients could be provided to users as ancillary tables
- However:
  - For climate use, bias corrections MUST be physically based
    - "Tuning" puts data independence at risk
    - Climate signals could be "tuned" out
  - Therefore
    - We should only put empirical correction into L1b as a last resort
    - We may provide empirical coefficients as ancillary tables
- For V5 the goal is to derive BETTER physically based coefficients
  - Try to get CLOSER agreement with empirical coefficients
  - Then use mostly model-based + a few empirical substitutes





### **Backup Slides**

- Gain variations
- AMSU & AIRS obs & sim vs. scan
- Sim[AIRS] vs. Sim[ECMWF]
- Obs-Sim: AIRS vs. ECMWF
- Scan bias correction coefficients
- Empirical scan bias correction





#### **AMSU Gain Variation: Ch. 1-3**

Channels 1-2 show only minor orbital gain variation

Channel 3 shows minor gain decline: about 1% per year

#### Shown: calibration coefficient $a_1 \approx 1/gain$







#### AMSU Gain Variation: Ch. 7-9

#### Shown: calibration coefficient a₁ ≈ 1/gain

# Only minor gain changes for these channels








#### **AMSU Gain Variation: Ch. 10-12**

#### Shown: calibration coefficient a₁ ≈ 1/gain

# Only minor gain changes for these channels








#### **AMSU Gain Variation: Ch. 13-15**


#### Shown: calibration coefficient a₁ ≈ 1/gain

# Negligible gain changes for these channels






#### AMSU & AIRS obs & sim vs. scan: Ch. 5















































































obs





























# obs-sim[AIRS] vs. obs-sim[ECMWF]







# obs-sim[AIRS] vs. obs-sim[ECMWF]







# obs-sim[AIRS] vs. obs-sim[ECMWF]

